



△ B Right hand side fork bottom's dimensions and left hand side fork bottom's dimensions are symmetrical

This document is confidential and must not be copied, with or without written permission, and the contents thereof must not be imparted to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.

ISO 2768mk	Dev. (mm)
±0.10	±0.10
±0.15	±0.15
±0.20	±0.20
±0.30	±0.30
±0.40	±0.40
±0.50	±0.50
±0.60	±0.60
±0.80	±0.80
±1.00	±1.00
±1.50	±1.50
±2.00	±2.00
±3.00	±3.00
±4.00	±4.00
±5.00	±5.00
±6.00	±6.00
±8.00	±8.00
±10.00	±10.00
±15.00	±15.00
±20.00	±20.00
±30.00	±30.00
±40.00	±40.00
±50.00	±50.00
±60.00	±60.00
±80.00	±80.00
±100.00	±100.00
±150.00	±150.00
±200.00	±200.00
±300.00	±300.00
±400.00	±400.00
±500.00	±500.00
±600.00	±600.00
±800.00	±800.00
±1000.00	±1000.00

Basic size (mm)	Dev. (mm)
0-10	±0.10
10-30	±0.15
30-50	±0.20
50-70	±0.25
70-100	±0.30
100-150	±0.40
150-200	±0.50
200-300	±0.60
300-400	±0.80
400-500	±1.00
500-600	±1.20
600-800	±1.50
800-1000	±2.00

Date	2019-11-13	Drawn	MOMO	Approved	TAN	Format	A1	Scale	1:1	Company	FGR_300, FGR_301			
Material	Heat treatment		Surface treatment											
Designation (swedish)	Dimensions										Drawing number	FGR_250.	Revision	B
Designation (english)	Front fork superbike													